

EA510HC



IR temperature measurement

Embedded medical grade IR thermal module, real-time report precisely temperature, error rate only ±0.3°C.



Anti-Microbial ant Disinfectant-Ready

Material of housing meet JISZ2801 Anti-Microbial standard, can afford wiping by alcohol and sterilized water. From inside to outside, stop cross-infection.



Superior performance

Advanced Octa-core new architecture processor, boost performance while reduced power consumption. High efficiency antenna design, seamless WIFI roaming, and wide LTE frequency coverage, present you best transfer experience.



Advance giant screen

5.7" giant bezel-less HD screen, assist medical personnel grab all information in a glance. Ultra-high brightness touch screen delivers clear vision even under sunlight.



Efficient intercommunication

Pre-installed network-based voice intercom system, teamwork is accessible by anyone, any time, any where. Voice command and TTS (text-to-speech) release your hand to save more lives.



Device management tools

U-Home, a series device management tools for injecting your new power.

- 1.U-setting: Savvy way for massive deployment
- 2.Scanwedge: All scan setting you needed.
- 3.AutoInstall: Pre-install and start up, everything automatic
- 4.FeatureSetting:Inspiration settings, only at Unitech.

Unitech Europe

Tilburg, The Netherlands • Tel.: +31 (0)13 460 9292 • Email: Info@eu.ute.com • Website: http://eu.ute.com



EA510HC

version 1.0 SPECIFICATIONS

PERFORMANCE CHARACTERISTICS		
CPU	Octa-core process	
Memory	RAM: 2GB, ROM:16GB RAM: 4GB, ROM:64GB(Optional)	
O.S.	Android 9.0	

PHYSICAL CH	IARACTERISTICS				
Display	5.7" TFT-LCD 720*1440 pixels 1080* 2160 pixels (Optional)				
Touchpanel	Ultra sensitive capacitive touch panel, works with gloves and wet fingers; Corning® Gorilla® Glass; Multi-touch				
Dimensions (L×W×H)	162.6mm× 76mm×13.6mm 6.4in× 3in× 0.53in				
Weight	250g/8.8oz (include battery)				
Power	Rechargeable 3.85V 4300mAh lithium polymer battery pack(Typical Operation time ≥10 hours) Support QC4.0 quick charge, charging time less than 3 hours				
Micro-SD	Micro-SD card,Up to 256GB extensions				
SIM	2×Nano-SIM slots				
Notification	LED, Speaker, Vibrator				
Buttons	Scan button ×2, Power button, Volume +/- button, User definable button				
Audio	Dual-microphone support with noise cancellation,high quality speaker, PTT headset support; cellular circuit switch voice				

ENVIRONMENTAL				
Operating Temperature	- 20°C ~ 60°C (-4°F~140°F)			
Storage Temperature	- 40°C ~ 70°C (-40°F~158°F)			
Humidity	5%RH ~ 95%RH(non condensing)			
Drop Specification	Multiple 5 ft./1.5 m drops on concrete across full operating temperature range.			
Tumble Specification	400 roller drops of 1m, with a frequency of 10 roller test per minutes			
Thermal Shock	- $40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (-40°F~158°F) rapid transition			
Sealing	IP67			
ESD	±15kV air discharge; ±8kV direct discharge			

DATA CAPTURE				
Scanning	1D/2D imager			
Camera	Front - 5MP Rear - 13MP auto-focus color rear camera with flash			
NFC	ISO 14443 Type A and B; FeliCa/Mifare and ISO 15693 cards; Reader mode, P2P mode, Card Emulation mode Apple Enhanced Contactless Polling(ECP)			

WIRELESS WAN DATA AND VOICE COMMUNICATIONS

Support Vo-LTE HD video voice call

Radio Frequency Band	TD-LTE(B34/B38/B39/B40/B41) FDD-LTE(B1/B2/B3/B4/B5/B7/B8/B12/B17/B19/B20/B28A/B28 WCDMA(B1/B2/B4/B5/B8) TD-SCDMA(B34/B39) CDMA2000 1x EV-DO Rev.A BC0 (800MHz) CDMA 1x GSM/EDGE/GPRS(850/900/1800/1900)
GPS	Concurrent GPS; GLONASS; Gallileo; BeiDou, and A-GPS

WIRELESS LAN			
WIFI	IEEE 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w		
Data Rates	5GHz:802.11a/n/acup to 866.7Mbps 2.4Ghz:802.11b/g/n up to 300Mbps		
Operating Channels	2.4G: 1-13(Depend on regulatory rules & certification agency) 5G: 36,38,40,42,44,46,48,52,56,60,64,100,104, 108,112,116,120,124,128,132,136,140,149,153, 157,161,165		
Security and Encryption	WEP;WPAWPA2-PSK(TKIP and AES);WAPI-PSK-EAP- TTLS, EAP-TLS,PEAP-MSCHAPv2,PEAP-LTS,PEAP- GTC,PWD, SIM, AKA		
Fast Roaming	PMKID caching, 802.11r. OKC		

MID	ELE	00	DΛ	M.
VVIIN		.00	гΑ	N

Vo-LTE

BT4.2 + BR/EDR + BLE

INTERACTIVE SENSOR

Acceleration sensor, light sensor, proximity sensor,3-axis geomagnetic sensor, fingerprint sensor

Optional Accessories









Single-slot Cradle

Hand Strap 4 slots battery charger

5 chains multi-function cradle

unitec because we care